## AMENDMENTS TO THE CLAIMS

 (Currently Amended) An organic electroluminescent device comprising a substrate and at least one organic layer containing a light-emitting layer between a pair of electrodes, wherein the light-emitting layer contains at least one host material,

wherein the organic electroluminescent device contains a compound emitting fluorescence at a time that voltage is applied, and a light emission at the time that voltage is applied is mainly derived from a light emission from the fluorescent compound, and

an external quantum efficiency of the device is 6% to 15.8% or more;

wherein the compound emitting fluorescence is represented by one of the following formulae (1)-(5):

Docket No.: 1982-0258PUS1

Art Unit: 2879

Page 2 of 10

 Application No. 10/566,723
 Docket No.: 1982-0258PUS1.

 Amendment dated November 12, 2009
 Art Unit: 2879

 Response to Office Action of August 12, 2009
 Page 3 of 10

wherein R<sup>101</sup>, R<sup>102</sup>, R<sup>103</sup>, R<sup>103</sup>, R<sup>104</sup>, R<sup>105</sup>, R<sup>106</sup>, R<sup>106</sup>, R<sup>107</sup>, R<sup>108</sup>, R<sup>109</sup>, R<sup>109</sup>, R<sup>101</sup>, R<sup>201</sup>, R<sup>202</sup>, R<sup>203</sup>, R<sup>204</sup>, R<sup>205</sup>, R<sup>206</sup>, R<sup>207</sup>, R<sup>208</sup>, R<sup>301</sup>, R<sup>302</sup>, R<sup>303</sup>, R<sup>304</sup>, R<sup>305</sup>, R<sup>306</sup>, R<sup>307</sup>, R<sup>308</sup>, R<sup>309</sup>, R<sup>309</sup>, R<sup>310</sup>, R<sup>311</sup>, R<sup>312</sup>, R<sup>401</sup>, R<sup>402</sup>, R<sup>403</sup>, R<sup>404</sup>, R<sup>405</sup>, R<sup>406</sup>, R<sup>406</sup>, R<sup>407</sup>, R<sup>408</sup>, R<sup>409</sup>, R<sup>410</sup>, R<sup>411</sup>, R<sup>412</sup>, R<sup>501</sup>, R<sup>502</sup>, R<sup>503</sup>, R<sup>504</sup>, R<sup>505</sup>, R<sup>506</sup>, R<sup>507</sup>, R<sup>508</sup>, R<sup>509</sup>, and R<sup>510</sup> each individually represents a hydrogen atom, an alkyl group, an alkenyl group, an alkynyl group, an aryl group, an amino group, an alkoxy group, an aryloxycarbonyl group, an acylamino group, an alkoxycarbonylamino group, an acylamino group, an alkoxycarbonylamino group, an arylthio group, an alkoxycarbonylamino group, a sulfonylamino group, a sulfamoyl group, a sulfonyl group, a ureido group, a phosphoric acid amido group, a hydroxyl group, a mercapto group, a halogen atom, a cyano group, a sulfo group, a carboxyl group, a nitro group, a silfo group, a sulfino group, a sulfino group, a hydroxyl group, a silfo group, or a silfloxy group, with the exception that wherein R<sup>104</sup> and R<sup>109</sup> do not represent a bromine atom group.

- 2. (Original) The organic electroluminescent device according to claim 1, wherein an internal quantum efficiency of the organic electroluminescent device is 30% or more.
- 3. (Original) The organic electroluminescent device according to claim 1 or 2, wherein the organic electroluminescent device contains an amplifying agent performing a function of amplifying a number of singlet excitons generated at the time that voltage is applied, thus amplifying an intensity of the light emission.
- (Previously Presented) The organic electroluminescent device according to claim 1, wherein a maximum light-emitting wavelength from the compound emitting fluorescence is 580 nm or less.
- (Previously Presented) The organic electroluminescent device according to claim 1, wherein the host material is a complex.

Application No. 10/566,723 Amendment dated November 12, 2009 Response to Office Action of August 12, 2009

6. (Cancelled)

(Previously Presented) The organic electroluminescent device according to claim 1,
 wherein the organic electroluminescent device has an electron-transporting layer, and the

electron-transporting layer contains a non-complex compound.

8. (Previously Presented) The organic electroluminescent device according to claim 3,

wherein the amplifying agent is a transition metal complex.

9. (Previously Presented) The organic electroluminescent device according to claim 3,

wherein a concentration of the amplifying agent contained in the light-emitting layer is 9 weight

% or less.

10. (Previously Presented) The organic electroluminescent device according to claim 3,

wherein a difference between the maximum light-emitting wavelength of the compound emitting

fluorescence at the time that voltage is applied, and a maximum light-emitting wavelength of the

amplifying agent, is 70 nm or less.

11. (Previously Presented) The organic electroluminescent device according to claim 3,

wherein a difference between the maximum light-emitting wavelength of the amplifying agent, and an absorption maximum wavelength of the compound emitting fluorescence at the time that

and an assorption maximum wavelength of the compound clinicing neorescence at the time the

voltage is applied, is -20 nm or more.

12. (Previously Presented) The organic electroluminescent device according to claim 1,

wherein the organic electroluminescent device has a hole-transporting layer, the light-emitting

layer and the electron-transporting layer, and a light emission from the compound emitting

fluorescence is 80% or more of a total light emission obtained from the organic

electroluminescent device.

Docket No.: 1982-0258PUS1

Art Unit: 2879

Page 4 of 10

Application No. 10/566,723 Amendment dated November 12, 2009

Docket No.: 1982-0258PUS1 Art Unit: 2879 Response to Office Action of August 12, 2009 Page 5 of 10

13. (Currently Amended) The organic electroluminescent device according to claim 1, wherein the organic electroluminescent device has [[the]] a hole-transporting layer, the lightemitting layer and [[the]] an electron-transporting layer, and has neither a hole blocking layer nor an exciton blocking layer between the light-emitting layer and the electron-transporting layer.

- 14. (Currently Amended) The organic electroluminescent device according to claim 3. wherein the organic electroluminescent device has [[the]] a hole-transporting layer, the lightemitting layer and [[the]] an electron-transporting layer, and the light-emitting layer has at least one alternately laminated structure including a layer containing at least one compound emitting fluorescence at a time that voltage is applied and a layer containing at least one amplifying agent.
- 15. (Original) The organic electroluminescent device according to claim 14, wherein the light-emitting layer has an alternately laminated structure of ten or more layers.